



> PRINT > COPY > SCAN > FAX

FS-1030MFP
FS-1030MFP/DP
FS-1130MFP

A4 MONOCHROME
MULTIFUNCTIONALS

PROFESSIONAL AND RELIABLE MULTIFUNCTIONALS



- > Up to 30 pages per minute in A4
- > Time to first copy - 6.9 seconds
- > 5-line LCD display for ease of use
- > Print, copy, scan and fax* functionality as standard
- > 50-sheet document processor scans double-sided documents**
- > Copy double-sided ID-cards on a single sheet of paper

*Only for FS-1130MFP **Not available for FS-1030MFP

The standard functionality delivered by these compact A4 MFPs will increase the productivity of any office workgroup. Get print and copy speeds of up to 30 pages per minute and a fast time to first print of only 6 seconds. These devices feature a large capacity document processor that scans double-sided originals for an enhanced document workflow.



ECOSYS stands for ECOlogy, ECONomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. KYOCERA's long-life components cost you and the environment less.

GENERAL

Technology: KYOCERA ECOSYS Laser

Control panel display: 5 line LCD display

Engine speed: Up to 30 pages A4 per minute

Resolution: 1,200 dpi quality (1,800 x 600 dpi, print), 600 x 600 dpi, 256 greyscales (scan/copy)

Duty cycle:

Maximum: 20,000 pages per month
Maximum Average: 3,333 pages per month
Average: 2,000 pages per month

Warm-up time: Approx. 20 seconds or less

Time to first print: Approx. 6 seconds or less

Time to first copy: Approx. 6.9 seconds

CPU: PowerPC 440/667 MHz

Memory: Standard 256 MB, max. 768 MB

Standard interface: USB 2.0 (Hi-Speed), USB Host, Fast Ethernet 10/100Base-TX, slot for optional CompactFlash® card, slot for optional print server (not in FS-1130MFP)

Integrated accounting: 20 department codes

Dimensions (W x D x H)

FS-1030MFP: 494 x 410 x 366 mm

FS-1030MFP/DP, FS-1130MFP: 494 x 430 x 448 mm

Weight

FS-1030MFP: Approx. 15 kg

FS-1030MFP/DP, FS-1130MFP: Approx. 18 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption FS-1030MFP, FS-1030MFP/DP FS-1130MFP

Copying/Printing: 480 W 482 W

Ready-mode: 78 W 83 W

Sleep-mode: 7.8 W 10.6 W

Auto-power-off-mode: 0.5 W or less 0.5 W or less

Noise (sound pressure level ISO 7779 / ISO 9296):

Copying/Printing: Half-speed mode 49 dB(A)

Copying/Printing: Full-speed mode 54 dB(A)

Stand-by (Ready-mode): 30 dB(A)

Safety standards: TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 50-sheet multi-purpose tray, 60–220 g/m², A4, A5, A6, B5, Letter, Legal, Folio, envelopes, Custom (70 x 148 to 216 x 356 mm) 250-sheet universal paper cassette, 60–120 g/m², A4, A5, A6, B5, Letter, Legal, Folio, Custom (105 x 148 to 216 x 356 mm)

Max. input capacity with options: 800 sheets

Duplex unit: Duplex as standard supports 60–105 g/m²

Platen glass: Up to 216 x 356 mm

Reversing document processor (not available in FS-1030MFP): 50-sheet, simplex scan 50–120 g/m², duplex scan 50–110 g/m², A4, A5, B5, Letter, Legal, Custom (140 x 210 to 216 x 356 mm)

Output capacity: Max. 150 sheets face-down

PRINT FUNCTIONS

Controller language: PRESCRIBE IIe

Emulations: PCL6 (5c/XL), KPDL 3 (PostScript 3-compatible), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PDF Direct Print, XPS Direct Print (requires memory expansion)

Operating systems: All current Windows operating systems, MAC OS X version 10.4 or higher, Unix, Linux as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL 6, HP-compatible) + 8 (Windows Vista), 101 (KPDL3), 1 bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

Features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3 and Private Print (requires memory expansion)

COPY FUNCTIONS

Max. original size: A4/Legal

Continuous copying: 1–999

Zoom range: 25–400% in 1% steps

Preset magnification ratios: 7 Reductions / 5 Enlargements

Exposure mode: Auto, manual: 7 steps

Image adjustments: Text + photo, text, photo

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail, Scan-to-FTP (FTP over SSL), Scan-to-SMB, Scan to USB Host, TWAIN (USB), WSD (WIA) scan (USB)

Scan speed:** 35 ipm (300 dpi, A4, b/w), 14 ipm (300 dpi, A4, colour)

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales)

Max. scan size: A4, Legal

Original recognition: Text, photo, text + photo, for OCR

File types: TIFF, PDF, JPEG, XPS

Compression method: MMR/JPEG

Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi-send (e-mail, fax, SMB/FTP folder, print) at once

FAX FUNCTIONS (FS-1130MFP ONLY)

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps

Transmission speed: Less than 3 seconds

Scanning speed: 2.5 seconds

One-touch dial: 22 numbers

Address book: 100 entries

Scanning density

Normal: 8 dot/mm x 3.85 lines/mm

Fine: 8 dot/mm x 7.7 lines/mm

Superfine: 8 dot/mm x 15.4 lines/mm

Ultrafine: 16 dot/mm x 15.4 lines/mm

Maximum original size: A4, Legal

Compression method: JBIG, MMR, MR, MH

Memory reception: 256 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast, memory reception

OPTIONS

Paper handling

PF-120 Paper feeder: Max. 250 sheets, 60–120 g/m², A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 297 mm)

Memory upgrade: MDDR2-256: 256 MB; MDDR2-512: 512 MB

CompactFlash® card: CF-4 (4 GB) for printing forms, fonts, logos, macro storage

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available

Optional interfaces (FS-1030MFP, FS-1030MFP/DP only)

PS159: Wireless LAN (802.11b/g/n)

PS1109 Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)

PS129 Fibre Optic: 100BaseFX (SC)

PS1129 Gigabit Fibre Optic: 1000BaseSX (SC)

CB-120: Wooden desk with storage capacity, including castors (wheels)

CONSUMABLES

Average continuous toner yield in accordance with ISO /IEC 19752

TK-1130 Toner-Kit: Microfine toner for 3,000 pages A4
Capacity of starter toner is 1,000 pages A4

WARRANTY

2-year warranty*** as standard. KYOCERA guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

KYO LIFE Up to 5-year on-site warranty extensions available for printer and options.



KYOCERA Document Solutions (UK) Ltd,
Eldon Court, 75 - 77 London Road, Reading RG1 5BS
Tel: 0118 931 1500 – Fax: 0118 931 1108
www.kyoceradocumentsolutions.co.uk – info@duk.kyocera.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. **Features/performance which requires a document processor are not offered by the FS-1030MFP. ***Depending on the country.

YOUR KYOCERA BUSINESS-PARTNER

 **KYOCERA**
Document Solutions